



## TEST REPORT

Product Name: Intelligent person  
Trademark: MMC  
Model Number: L1  
Prepared For: MicroMultiCopter Innovation Technology Co., Ltd.  
Address: Room 1701-5, Building 1, Land Plaza, No. 399, Jiashan Ave-nue, Luoxing Street, Jiaxing City, Zhejiang Province  
Manufacturer: MicroMultiCopter Innovation Technology Co., Ltd.  
Address: Room 1701-5, Building 1, Land Plaza, No. 399, Jiashan Ave-nue, Luoxing Street, Jiaxing City, Zhejiang Province  
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.  
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China  
Sample Received Date: May. 07, 2025  
Sample tested Date: May. 07, 2025 to Jun. 04, 2025  
Issue Date: Jun. 04, 2025  
Report No.: CTB25050708703RH01  
Test Standards: EN IEC 62311:2020  
EN 50665:2017  
Test Results: PASS  
Compiled by: Reviewed by: Approved by:

Zhou Kui

Arron Liu

Bin Mei

Zhou KuiArron LiuBin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "\*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

## TABLE OF CONTENT

Test Report Declaration	Page
1. <b>VERSION</b> .....	<b>3</b>
2. <b>PRODUCT INFORMATION AND TEST SETUP</b> .....	<b>4</b>
2.1 Product Information .....	4
3. <b>HEALTH REQUIREMENTS</b> .....	<b>5</b>
3.1 Limits .....	5
3.2 Exposure Evaluation .....	6
4. <b>EUT PHOTOGRAPHS</b> .....	<b>7</b>

(Note: N/A means not applicable)

**1. VERSION**

Report No.	Issue Date	Description	Approved
CTB25050708703RH01	Jun. 04, 2025	Original	Valid



## 2. PRODUCT INFORMATION AND TEST SETUP

### 2.1 Product Information

Model(s):	L1
Model Description:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850MHz/ 5 channel IEEE 802.11n/ac/ax(40M): 5725MHz ~5850MHz/ 2 channel IEEE 802.11ac/ax(80M): 5725MHz ~5850MHz/ 1 channel
Max. RF output power:	WiFi (5.8G): 11.71dBm
Type of Modulation:	WiFi (5.8G): OFDM, OFDMA
Antenna installation:	WiFi (5.8G): Internal antenna
Antenna Gain:	WiFi (5.8G): ANT1: 1.0dBi, ANT2: 1.0dBi
Ratings:	DC 5V charging from adapter DC 16.4V by battery

### 3. HEALTH REQUIREMENTS

#### 3.1 Limits

According to Council Recommendation: the criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

Reference levels for electric, magnetic and electromagnetic fields (0Hz to 300GHz, unperturbed RMS values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density Seq (W/m2)
0-1 Hz	-	$3.2 \times 10^4$	$4 \times 10^4$	-
1-8 Hz	10000	$3.2 \times 10^4 / f^2$	$4 \times 10^4 / f^2$	-
8-25 Hz	10000	$4000 / f$	$5000 / f$	-
0.025-0.8 kHz	$250 / f$	$4 / f$	$5 / f$	-
0.8-3 kHz	$250 / f$	5	6.25	-
3-150 kHz	87	5	6.25	-
0.15-1 MHz	87	$0.73 / f$	$0.92 / f$	-
1-10 MHz	$87 / f^{1/2}$	$0.73 / f$	$0.92 / f$	-
10-400 MHz	28	0.073	0.095	2
400-2000 MHz	$1.375 f^{1/2}$	$0.0037 f^{1/2}$	$0.0046 f^{1/2}$	$f / 200$
2-300 GHz	61	0.16	0.2	10

Note:

1. f as indicated in the frequency range column.
2. For frequencies between 100 kHz and 10 GHz, Seq, E<sup>2</sup>, H<sup>2</sup> and B<sup>2</sup> are to be averaged over any six-minute period.
3. For frequencies exceeding 10 GHz, Seq, E<sup>2</sup>, H<sup>2</sup> and B<sup>2</sup> are to be averaged over any  $68 / f^{1.05}$  minute period (f in GHz).

### 3.2 Exposure Evaluation

From Council Recommendation 1999/519/EC table 2, the maximum power density is 10 W/m<sup>2</sup>.

Power density (S) is calculated by the following formula:

$$S = PG * \text{Duty factor} / 4\pi R^2$$

P = Peak Power Input to antenna (Watts)

G = Antenna Gain (numeric)

R = distance to the center of radiation of antenna (in meter) = 0.2 m

Note:

1)  $P \text{ (Watts)} = (10^{(\text{dBm} / 10)}) / 1000$

2)  $G \text{ (Antenna gain in numeric)} = 10^{(\text{Antenna gain in dBi} / 10)}$

3) Duty factor = 1.0

4)  $\pi = 3.142$

#### 5.8G WIFI ANT1:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (W)	Duty factor	Calculated RF Exposure (W/ m <sup>2</sup> )	Limit (W/ m <sup>2</sup> )
1	1.2589	7.42	0.0055	1	0.0138	10

#### 5.8G WIFI ANT2:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (W)	Duty factor	Calculated RF Exposure (W/ m <sup>2</sup> )	Limit (W/ m <sup>2</sup> )
1	1.2589	7.51	0.0056	1	0.0141	10

#### 5.8G WIFI MIMO:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (W)	Duty factor	Calculated RF Exposure (W/ m <sup>2</sup> )	Limit (W/ m <sup>2</sup> )
1	1.2589	10.71	0.0118	1	0.0295	10



#### 4. EUT PHOTOGRAPHS

Refer to Report No.: CTB25050708703RE03 for EUT external and internal photos.

**.\*\*\*\*\* END OF REPORT \*\*\*\*\***