



Thunder P1

Transmit Your Voice as Loud as a Thunder

Thunder P1 megaphone uses a custom tweeter with a maximum of 120dB and an effective audible distance of up to 600m. Its FPV camera is equipped with a new generation of image transmission system to monitor the scene in real time. An integrated single-axis gimbal can be used as needed to adjust the camera pitch angle at any time, and a high signal-to-noise ratio microphone is deployed to reduce the influence of the environment and ensure a clear sound. Thunder P1 is useful for scenes such as on-site rescue, anti-terrorism and riot prevention.

KEY FEATURES

- A custom tweeter with a maximum of 120dB and an effective audible distance of up to 600m
- FPV camera to monitor the scene in real time
- Integrated single-axis gimbal to adjust the camera pitch angle at any time
- High signal-to-noise ratio microphone to reduce the influence of the environment and ensure a clear sound.

SPECIFICATIONS

Size	217.5*133.9*191.7mm
Weight	800g
Working Temperature	-20 C ~60 C
Storage Temperature	-30 C ~70 C
Max. Volume	120dB
Audible Distance	600m
Video Resolution	0.3 million
Lens	f=3.6mm
Angle Range	0°~90°
Size	75*56.5*24.5mm
Weight	130g
Sensitivity	-32dB
SNR (Signal to Noise Ratio)	Over 60dB

CONTACT

MMC Tech Park, No.1 Yihe Road, Shilong Community, Shiyuan Street, Bao'an District, Shenzhen, PR China,

Web: www.mmcuav.com Tel: +86 4008082021

Email: info@mmcuav.com